



**NOTES:**

1. THE SIGN FACE SHALL BE 12" X12" AND FABRICATED FROM .080 ALUMINUM SHEET WITH 1 1/2" RADIUS CORNERS.
2. FONT STYLE USED IS HANDEL GOTHIC BT CAPITAL FONTS
3. THE SIGN FACE SHALL HAVE A WHITE 3M DIAMOND GRADE REFLECTIVE SHEETING (DG<sup>3</sup> 4090 SERIES OR EQUIVALENT) APPLIED AS A BACKGROUND TO THE ALUMINUM PLATES.
4. LETTERING SHALL BE DONE ONE OF THE FOLLOWING WAYS:
  - A. 3M SCOTCHLITE ACRYLIC, TRANSPARENT, ELECTRONIC CUTTABLE FILM (RED 1172 SERIES) INVERSE CUT TO ALLOW WHITE REFLECTIVE BACKGROUND TO SHOW THROUGH.
  - B. SCREEN PRINTED USING 3M 880I OR 880-00 SERIES TRAFFIC SIGN RED TRANSLUCENT INK.

BOTH PROCESSES ( A OR B ) WILL ACCOMPLISH A RED FIELD WITH WHITE COPY.
5. ALL SIGN IMAGING SHALL BE IN COMPLIANCE WITH THE REFLECTIVE SHEETING MANUFACTURES MATCH COMPONENT SYSTEM.
6. TO BE INSTALLED 5 FEET ABOVE GRADE, POST SHALL BE 12" TO 18" FROM BACK OF CURB OR BACK OF SIDEWALK AND MUST FACE THE ONCOMING TRAFFIC.

