

GENERAL NOTES:

- ① NOTE USED.
- ② PROPERTY OWNER/MANAGEMENT PADLOCK
- ③ FIRE DEPT. PADLOCK SHALL BE ACCESSIBLE FROM BOTH SIDES OF GATE.
- ④ APPROVED FIRE LANE SIGNS WITH REFLECTIVE BACKGROUND, PLACED BACK TO BACK AND FASTENED ON ALL 4 CORNERS. 1/4" X 1 1/2" MOUNTING STRAPS.
- ⑤ FIRE LANE STRIPING SHALL BE PROVIDED AT EACH MANUAL GATE.
- ⑥ THE MINIMUM OVERALL WIDTH OF THE GATE OPENING SHALL BE 20 FT.
- ⑦ WELD MODIFIED L-BRACKET TO GATE FRAME. ROUND ALL EDGES. (TYPICAL 2 PLACES)
- ⑧ LOCKING BAR LENGTH IS DETERMINED BY THE FRAME WIDTH AND THE GAP WIDTH BETWEEN THE 2 GATES. REMOVE ALL SHARP EDGES / ROUND ALL CORNERS.
- ⑨ APPROVED FIRE DEPT. ACCESS SIGN WITH WHITE 3M DIAMOND GRADE DG³ BACKGROUND PLACED BACK TO BACK.
- ⑩ 24" X 36" CONCRETE POST FOOTINGS

