

Do not clean with pressure washer—wipe down with detergent and wipe rinse.

o Gasoline Powered Fans:

- | | |
|----------------------|-------------------------------|
| • Screw, nuts, bolts | Inspect and tighten |
| • Safety guards | Inspect and clean |
| • Foot pads | Inspect for wear |
| • Blade | Inspect for damage |
| • Oil level | Check and fill as needed |
| • Fuel level | Fill as needed |
| • Air filter | Service as required |
| • Overall condition | Check for damage, leaks, ect. |
| • Start Engine | Run 1 – 2 minutes |

Do not clean with pressure washer—wipe down with detergent and wipe rinse.

Rescue Tool:

- Ladder Company Engineer – The following operations will be performed by the engineer daily.

o Checklist:

- | | |
|------------------------|------------------------------|
| ▪ Screws, nuts, bolts | Inspect and tighten |
| ▪ Accessories | Check inventory |
| ▪ Holster & tool pouch | Inspect for abnormal wear |
| ▪ Air tank | Inspect & fill to 3000 psi |
| ▪ Harness straps | Inspect & repair |
| ▪ Hose & couplings | Inspect for proper functions |

- Oil air hammer each time after use. (3 drops)
- Clean with dry rag.
- Do not use petroleum based products on couplings for lubrication.

Approved:  _____ 10/5/04
 Robert McKibben, Fire Chief Date